

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : RE-GEN™ Universal

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only  
Use of the substance/mixture : Dental Adhesive

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier:

Please provide the European importer, only representative, downstream user or distributor contact details:

Supplier name:

Street address/P.O. Box

Country ID/Postal code

Telephone number

Manufacturer:

Inter-Med, Inc. / Vista Dental Products

2200 South Street

Racine, WI 53404

T: (877)-418-4782

info@vista-dental.com

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (North America) / +1 (703) 527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335

Full text of H-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May damage fertility or the unborn child. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Signal word (CLP)	: Danger
Contains	: 2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester; 1,2,4,5-Benzenetetracarboxylic acid, 1,4-bis[2-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-1-[[2-(methyl-1-oxo-2-propen-1-yl)oxy]methyl]ethyl] ester; Benzoic acid, 4-(dimethylamino)-, ethyl ester
Hazard statements (CLP)	: H225 - Highly flammable liquid and vapour. H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H360 - May damage fertility or the unborn child.
Precautionary statements (CLP)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P235 - Keep cool. P280 - Wear eye protection, protective gloves. P308+P313 - IF exposed or concerned: Get medical advice/attention.

### 2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester	CAS-No.: 1565-94-2 EC-No.: 216-367-7	20 – 25	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ethyl alcohol	CAS-No.: 64-17-5 EC-No.: 200-578-6 EC Index-No.: 603-002-00-5 REACH-no: 01-2119457610-43	18 – 22.5	Flam. Liq. 2, H225 Eye Irrit. 2, H319
1,2,4,5-Benzenetetracarboxylic acid, 1,4-bis[2-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-1-[[2-(methyl-1-oxo-2-propen-1-yl)oxy]methyl]ethyl] ester	CAS-No.: 148019-46-9	15 – 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335
2-Hydroxyethyl methacrylate	CAS-No.: 868-77-9 EC-No.: 212-782-2 EC Index-No.: 607-124-00-X	10 – 15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
10- Methacryloyloxydecyl dihydrogen phosphate (10-MDP)	CAS-No.: 85590-00-7	5 – 15	Eye Irrit. 2, H319 Skin Sens. 1, H317
Benzoic acid, 4-(dimethylamino)-, ethyl ester	CAS-No.: 10287-53-3 EC-No.: 233-634-3	< 1	Repr. 1B, H360 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse immediately with plenty of water for 15 minutes. Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May damage fertility or the unborn child.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Carbon dioxide. Alcohol resistant foam. Water spray.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour. On combustion, forms: carbon oxides (CO and CO <sub>2</sub> ). Nitrogen oxides. Phosphorus oxides. fluorinated compounds.
Explosion hazard	: Vapours may cause fire/explosion if source of ignition is present.
Hazardous decomposition products in case of fire	: Thermal decomposition can lead to the escape of irritating gases and vapours.

#### 5.3. Advice for firefighters

Protective equipment for firefighters	: Do not attempt to take action without suitable protective equipment.
---------------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep away from sources of ignition. Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Avoid breathing mist, spray, vapours.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

Emergency procedures	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Emergency procedures	: Eliminate all ignition sources if safe to do so. Stop leak without risks if possible. Prevent entry to sewers and public waters.
----------------------	--

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb spillage to prevent material damage.
- Methods for cleaning up : Remove all sources of ignition. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Notify authorities if product enters sewers or public waters. Collect all waste in suitable and labelled containers and dispose according to local legislation.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Flammable vapours may accumulate in the container.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Flammable vapours may accumulate in the container. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing spray, mist, vapours. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Provide local exhaust or general room ventilation.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Incompatible materials : Strong acids, strong bases and oxidation agents.

### 7.3. Specific end use(s)

See Heading 1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. National occupational exposure and biological limit values

Ethyl alcohol (64-17-5)	
Austria - Occupational Exposure Limits	
Local name	Ethanol
MAK (OEL TWA)	1900 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	3800 mg/m <sup>3</sup> (3x 60(Mow) min)
MAK (OEL STEL) [ppm]	2000 ppm (3x 60(Mow) min)
OEL C	3800 mg/m <sup>3</sup>
OEL C [ppm]	2000 ppm
Regulatory reference	BGBl. II Nr. 238/2018
Belgium - Occupational Exposure Limits	
Local name	Alcool éthylique # Ethanol

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
OEL TWA	1907 mg/m <sup>3</sup>
OEL TWA [ppm]	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	Етилов алкохол
OEL TWA	1000 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
Croatia - Occupational Exposure Limits	
Local name	Etanol; etil-alkohol
GVI (OEL TWA) [1]	1900 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	1000 ppm
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
PEL (OEL TWA)	1000 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	522 ppm
NPK-P (OEL C)	3000 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	1566 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 41/2020 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Ethanol (Ethylalkohol)
OEL TWA [1]	1900 mg/m <sup>3</sup>
OEL TWA [2]	1000 ppm
Regulatory reference	BEK nr 290 af 13/02/2021
Estonia - Occupational Exposure Limits	
Local name	Etanool (etüülalkohol)
OEL TWA	1000 mg/m <sup>3</sup>
OEL TWA [ppm]	500 ppm
OEL STEL	1900 mg/m <sup>3</sup>
OEL STEL [ppm]	1000 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	Etanoli
HTP (OEL TWA) [1]	1900 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	1000 ppm
HTP (OEL STEL)	2500 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	1300 ppm

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Alcool éthylique
VME (OEL TWA)	1900 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	1000 ppm
VLE (OEL C/STEL)	9500 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	5000 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Ethanol
AGW (OEL TWA) [1]	380 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Greece - Occupational Exposure Limits</b>	
Local name	Αιθνόλη
OEL TWA	1900 mg/m <sup>3</sup>
OEL TWA [ppm]	1000 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
Local name	ETIL-ALKOHOL
AK (OEL TWA)	1900 mg/m <sup>3</sup>
CK (OEL STEL)	3800 mg/m <sup>3</sup>
Megjegyzések (HU)	N (Irritáló anyagok, egyszerű fojtógázok, csekély egészségkárosító hatással bíró anyagok)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethanol [Ethyl alcohol]
OEL TWA [1]	1900 mg/m <sup>3</sup>
OEL TWA [2]	1000 ppm
OEL STEL [ppm]	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2020
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Etilspirts (etanols)
OEL TWA	1000 mg/m <sup>3</sup>

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Etanolis (etilo alkoholis)
IPRV (OEL TWA)	1000 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	500 ppm
TPRV (OEL STEL)	1900 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	1000 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Ethanol
MAC-TGG (OEL TWA)	260 mg/m <sup>3</sup>
MAC-15 (OEL STEL)	1900 mg/m <sup>3</sup>
Remark (MAC)	Kankerverwekkende stof. H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2021
<b>Poland - Occupational Exposure Limits</b>	
Local name	Etanol (alkohol etylowy)
NDS (OEL TWA)	1900 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Etanol (Álcool etílico)
OEL TWA [ppm]	1000 ppm
OEL STEL [ppm]	1000 ppm
Chemical category	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
Remark	A3 (Agente carcinogénico confirmado nos animais de laboratorio con relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	Alcool etilic/Etanol
OEL TWA	1900 mg/m <sup>3</sup>
OEL TWA [ppm]	1000 ppm
OEL STEL	9500 mg/m <sup>3</sup>
OEL STEL [ppm]	5000 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Etylalkohol (etanol)
NPHV (OEL TWA) [1]	960 mg/m <sup>3</sup>

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
NPHV (OEL TWA) [2]	500 ppm
NPHV (OEL STEL)	1920 mg/m <sup>3</sup>
NPHV (OEL STEL) [ppm]	1000 ppm
NPHV (OEL C)	1920 mg/m <sup>3</sup>
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	etanol (etilalkohol)
OEL TWA	960 mg/m <sup>3</sup>
OEL TWA [ppm]	500 ppm
OEL STEL	1920 mg/m <sup>3</sup>
OEL STEL [ppm]	1000 ppm
Remark (SI)	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 78/2019 z dne 20.12.2019
Spain - Occupational Exposure Limits	
Local name	Etanol (Alcohol etílico)
VLA-ED (OEL TWA) [1]	1910 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	1000 ppm
VLA-EC (OEL STEL)	1910 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	1000 ppm
Notes	s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: <a href="http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas">http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas</a> Base de datos de productos fitosanitarios <a href="http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf">http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf</a> ).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etanol
NGV (OEL TWA)	1000 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	500 ppm
KTV (OEL STEL)	1900 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	1000 ppm
Anmärkning (SE)	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA) [1]	1920 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1000 ppm
WEL STEL (OEL STEL)	5760 mg/m <sup>3</sup> (calculated)



# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Ethyl alcohol (64-17-5)	
WEL STEL (OEL STEL) [ppm]	3000 ppm (calculated)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanol
ACGIH OEL STEL [ppm]	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2021
2-Hydroxyethyl methacrylate (868-77-9)	
Lithuania - Occupational Exposure Limits	
Local name	Etilenglikolio metakrilo eteris
IPRV (OEL TWA)	20 mg/m <sup>3</sup>
Remark (LT)	J (jautrinantis poveikis)
Chemical category	Sensitizer
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses. EN 166

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Long sleeved protective clothing

##### Hand protection:

Chemically resistant protective gloves. EN 374

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow.
Appearance	: Clear.
Odour	: Odourless.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: For solids: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong acids, strong bases and oxidation agents.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)  
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

#### Ethyl alcohol (64-17-5)

LD50 oral rat	7060 mg/kg
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat	133.8 mg/l/4h

#### 2-Hydroxyethyl methacrylate (868-77-9)

LD50 oral rat	5050 mg/kg
LD50 dermal rabbit	> 3000 mg/kg

#### Benzoic acid, 4-(dimethylamino)-, ethyl ester (10287-53-3)

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitisation : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)  
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)  
Reproductive toxicity : May damage fertility or the unborn child.  
STOT-single exposure : May cause respiratory irritation.

#### 1,2,4,5-Benzenetetracarboxylic acid, 1,4-bis[2-[(2-methyl-1-oxo-2-propen-1-yl)oxy]-1-[[[(2-methyl-1-oxo-2-propen-1-yl)oxy]methyl]ethyl] ester (148019-46-9)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

#### Ethyl alcohol (64-17-5)

NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : No additional information available

#### 11.2.2. Other information

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : This material has not been tested for environmental effects.  
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)  
Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

#### Ethyl alcohol (64-17-5)

LC50 - Fish [1]	12 – 16 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 - Other aquatic organisms [1]	5012 mg/l 48 hours- daphnia
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Other aquatic organisms [1]	5012 mg/l waterflea
EC50 - Other aquatic organisms [2]	275 mg/l
ErC50 algae	275 mg/l Source: ECHA
ErC50 other aquatic plants	4432 mg/l
NOEC (acute)	9.6 mg/l Daphnia magna
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
NOEC chronic crustacea	9.6 mg/l

#### 2-Hydroxyethyl methacrylate (868-77-9)

LC50 - Fish [1]	213 – 242 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	227 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

#### Ethyl alcohol (64-17-5)

Partition coefficient n-octanol/water (Log Pow)	-0.32
---	-------

#### 2-Hydroxyethyl methacrylate (868-77-9)

BCF - Fish [1]	1.34 – 1.54
Partition coefficient n-octanol/water (Log Pow)	0.47

### 12.4. Mobility in soil

No additional information available

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.






## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
<b>14.2. UN proper shipping name</b>				
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
<b>Transport document description</b>				
UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II	UN 1993 Flammable liquid, n.o.s. (Ethyl alcohol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
II	II	II	II	II
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
Consult the associated transport regulations for available and applicable exceptions or exemptions.				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 274, 601, 640C  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001  
Mixed packing provisions (ADR) : MP19


# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

---

Portable tank and bulk container instructions (ADR) : T7  
Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28  
Tank code (ADR) : L1.5BN  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

### Transport by sea

Special provisions (IMDG) : 274  
Limited quantities (IMDG) : 1 L  
Excepted quantities (IMDG) : E2  
Packing instructions (IMDG) : P001  
IBC packing instructions (IMDG) : IBC02  
Tank instructions (IMDG) : T7  
Tank special provisions (IMDG) : TP1, TP28, TP8  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E  
Stowage category (IMDG) : B

### Air transport

PCA Excepted quantities (IATA) : E2  
PCA Limited quantities (IATA) : Y341  
PCA limited quantity max net quantity (IATA) : 1L  
PCA packing instructions (IATA) : 353  
PCA max net quantity (IATA) : 5L  
CAO packing instructions (IATA) : 364  
CAO max net quantity (IATA) : 60L  
Special provisions (IATA) : A3  
ERG code (IATA) : 3H

### Inland waterway transport

Classification code (ADN) : F1  
Special provisions (ADN) : 274, 601, 640C  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E2  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

### Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 274, 601, 640C  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T7  
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28  
Tank codes for RID tanks (RID) : L1.5BN  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7  
Hazard identification number (RID) : 33

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

##### France

###### Occupational diseases

Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

##### Germany

Employment restrictions : Observe restrictions according Act on the Protection of Working Mothers (MuSchG)  
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

WGK remark : Most stringent classification due to insufficient data

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Ethyl alcohol is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting : Ethyl alcohol is listed

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting : Ethyl alcohol is listed

giftige stoffen – Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting : Ethyl alcohol is listed

giftige stoffen – Ontwikkeling

##### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Full text of H- and EUH-statements

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

# RE-GEN™ Universal

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements	
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H360	May damage fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]		
Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360	Calculation method
STOT SE 3	H335	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.