

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Superb

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Adhesive used for restoration delivery

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Supplier:

Please provide the European importer, only representative, downstream user or distributor contact details:

Supplier name:

Street address/P.O. Box

Country ID/Postal code

Telephone number

Email address (this can be a general email for the competent person responsible for the SDS)

Manufacturer:

Inter-Med, Inc. / Vista Dental Products

2200 South Street

Racine, WI 53404

T: (877)-418-4782

#### 1.4. Emergency telephone number

Emergency number : 800-424-9300 (North America)  
+1 (703) 527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360
Full text of H statements : see section 16	

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May damage fertility or the unborn child.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : 2-hydroxyethyl methacrylate; 2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester; 10- Methacryloyloxydecyl dihydrogen phosphate (10-MDP); Benzoic acid, 4-(dimethylamino)-, ethyl ester

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H360 - May damage fertility or the unborn child.

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P201 - Obtain special instructions before use.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P235 - Keep cool.  
P280 - Wear protective gloves, eye protection.  
P308+P313 - IF exposed or concerned: Get medical advice/attention.  
P370+P378 - In case of fire: Use Water spray, dry extinguishing powder, foam, carbon dioxide (CO<sub>2</sub>), sand to extinguish.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Propenoic acid, 2-methyl-, (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] ester	(CAS-No.) 1565-94-2 (EC-No.) 216-367-7	15 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	15 - 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Bis[2-[(2-methyl-1-oxoallyl)oxy]ethyl] dihydrogen benzene-1,2,4,5-tetracarboxylate	(CAS-No.) 51156-91-3 (EC-No.) 257-023-6	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2 (EC Index-No.) 607-124-00-X	10 - 30	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317
10- Methacryloyloxydecyl dihydrogen phosphate (10-MDP)	(CAS-No.) 85590-00-7	7 - 13	Eye Irrit. 2, H319 Skin Sens. 1, H317
Acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) Not available	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Benzoic acid, 4-(dimethylamino)-, ethyl ester	(CAS-No.) 10287-53-3 (EC-No.) 233-634-3	0.5 - 1.5	Repr. 1B, H360 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Give artificial respiration if necessary. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Take off immediately all contaminated clothing. Rinse immediately with plenty of water for 15 minutes. Get medical advice if skin irritation persists.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes. If eye irritation persists: Get medical advice and attention.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May damage fertility or the unborn child.

Symptoms/effects after inhalation : Not expected to present a significant inhalation hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : Causes skin irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May cause irritation to the digestive tract.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Sand.

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : On combustion, forms: carbon oxides (CO and CO<sub>2</sub>).

Explosion hazard : May form flammable vapour-air mixture. Vapours may travel long distances along ground before igniting/flashing back to vapour source.

Reactivity in case of fire : Stable under normal conditions.

### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep away from open flames, hot surfaces and sources of ignition.

#### 6.1.1. For non-emergency personnel

Protective equipment : Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with eyes. Wear personal protective equipment. Avoid breathing vapours, mist.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical/ventilating/lighting equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage conditions : Store in a well-ventilated place. Keep cool.

Incompatible materials : None known.

### 7.3. Specific end use(s)

See Heading 1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Acetone (67-64-1)

#### EU - Occupational Exposure Limits

Local name	Acetone
IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
IOELV TWA (ppm)	500 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

#### Austria - Occupational Exposure Limits

Local name	Aceton
------------	--------

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Acetone (67-64-1)</b>	
MAK (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
MAK (ppm)	500 ppm
MAK Short time value (mg/m <sup>3</sup> )	4800 mg/m <sup>3</sup>
MAK Short time value (ppm)	2000 ppm
Regulatory reference	BGBI. II Nr. 186/2015
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Acétone # Aceton
Limit value (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Limit value (ppm)	500 ppm
Short time value (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Short time value (ppm)	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Ацетон
OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
OEL STEL (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
Notes	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.73 от 4 септември 2018 г.)
<b>Bulgaria - Biological limit values</b>	
Local name	Ацетон
Bulgaria - BLV	80 mg/l Биомаркер за експозиция/биомаркер за ефект: ацетон - Биологична среда: урина - Време на пробовземане: В края на експозицията или в края на работната смяна - Специфични ефекти: Няма
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.73 от 4 септември 2018 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Aceton
GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
GVI (granična vrijednost izloženosti) (ppm)	500 ppm
KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	3620 mg/m <sup>3</sup>
KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	1500 ppm
Naznake (HR)	Direktiva: 2000/39/EZ
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Aceton (2-Propanon)
Expoziční limity (PEL) (mg/m <sup>3</sup> )	800 mg/m <sup>3</sup>
Expoziční limity (PEL) (ppm)	336.8 ppm
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	1500 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (ppm)	631.5 ppm
Remark (CZ)	I (dráždí sliznice (oči, dýchací cesty) resp. kůži)
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (zapracovány změny č. 246/2018 Sb.)

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Acetone (67-64-1)</b>	
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Acetone (2-Propanon)
Grænseværdie (langvarig) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Grænseværdie (langvarig) (ppm)	250 ppm
Grænseværdie (kortvarig) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Grænseværdie (kortvarig) (ppm)	500 ppm
Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi)
Regulatory reference	BEK nr 655 af 31/05/2018
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Atsetoon (2-propanoon)
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	Vabariigi Valitsuse 18. septembri 2001. a määruse nr 293 (RT I, 30.11.2011, 5)
<b>Finland - Occupational Exposure Limits</b>	
Local name	Asetoni
HTP-arvo (8h) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
HTP-arvo (8h) (ppm)	500 ppm
HTP-arvo (15 min)	1500 mg/m <sup>3</sup>
HTP-arvo (15 min) (ppm)	630 ppm
Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Acétone
VME (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
VME (ppm)	500 ppm
VLE (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
VLE (ppm)	1000 ppm
Note (FR)	Valeurs réglementaires contraignantes
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
TRGS 900 Local name	Aceton
TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
TRGS 900 Occupational exposure limit value (ppm)	500 ppm
TRGS 900 Limitation of exposure peaks	2(l)
TRGS 900 Remark	AGS;DFG;EU;Y
TRGS 900 Regulatory reference	TRGS900
<b>Germany - Biological limit values (TRGS 903)</b>	
TRGS 903 Local name	Aceton
TRGS 903 Biological limit value	80 mg/l
TRGS 903 Remark	Aceton (Urin; Expositionsende bzw. Schichtende)
TRGS 903 Regulatory reference	TRGS 903
<b>Greece - Occupational Exposure Limits</b>	
Local name	Ακετόνη
OEL TWA (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
OEL STEL (mg/m <sup>3</sup> )	3560 mg/m <sup>3</sup>

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Acetone (67-64-1)</b>	
Regulatory reference	Π.Δ. 90/1999
<b>Hungary - Occupational Exposure Limits</b>	
Local name	ACETON (dimetil-ke-ton)
AK-érték	1210 mg/m <sup>3</sup>
CK-érték	2420 mg/m <sup>3</sup>
Megjegyzések (HU)	i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármat); EU1 (2000/39/EK irányelvben közölt érték)
Regulatory reference	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet a munkahelyek kémiai biztonságáról
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Acetone
OEL (8 hours ref) (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	500 ppm
Notes (IE)	IOELV
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
<b>Italy - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Acetons (2-propanons, dimetilketons)
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Acetonas
IPRV (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
IPRV (ppm)	500 ppm
TPRV (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
TPRV (ppm)	1000 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Luxembourg - Occupational Exposure Limits</b>	
Local name	Acétone
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	Mémorial A N° 684 de 2018
<b>Malta - Occupational Exposure Limits</b>	
Local name	Acetone
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	S.L.424.24 (L.N.57 of 2018)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Aceton
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Acetone (67-64-1)</b>	
Regulatory reference	Arbetsomstandighedenregeling 2018
<b>Poland - Occupational Exposure Limits</b>	
Local name	Aceton
NDS (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
NDSCh (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Acetona
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
OEL STEL (ppm)	750 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	Acetonă
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
Regulatory reference	Hotărârea nr. 584/2018
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Acetón (propanón)
NPHV (priemerná) (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
NPHV (priemerná) (ppm)	500 ppm
Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	acetón
OEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
OEL STEL (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
OEL STEL (ppm)	1000 ppm
Remark (SI)	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biolóška mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
<b>Spain - Occupational Exposure Limits</b>	
Local name	Acetona
VLA-ED (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
VLA-ED (ppm)	500 ppm
VLA-EC (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
VLA-EC (ppm)	750 ppm
Notes	VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Spain - Biological limit values</b>	
Local name	Acetona
Spain - BLV	50 mg/l Parámetro: Acetona - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Acetone (67-64-1)</b>	
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Aceton
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
nivågränsvärde (NVG) (ppm)	250 ppm
kortidsvärde (KTV) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
kortidsvärde (KTV) (ppm)	500 ppm
Anmärkning (SE)	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Acetone
WEL TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
WEL TWA (ppm)	500 ppm
WEL STEL (mg/m <sup>3</sup> )	3620 mg/m <sup>3</sup>
WEL STEL (ppm)	1500 ppm
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Aseton (2-própanón)
OEL (8 hours ref) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	250 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)
<b>Norway - Occupational Exposure Limits</b>	
Local name	Aceton
Grenseverdier (AN) (mg/m <sup>3</sup> )	295 mg/m <sup>3</sup>
Grenseverdier (AN) (ppm)	125 ppm
Merknader (NO)	E (EU har en veiledende grenseverdi for stoffet)
Regulatory reference	FOR-2018-08-21-1255
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Acetone
ACGIH TWA (ppm)	250 ppm
ACGIH STEL (ppm)	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2019
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	ACETONE
Biological Exposure Indices (BEI)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2019
<b>2-hydroxyethyl methacrylate (868-77-9)</b>	
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Etilenglikolio metakrilo eteris
IPRV (mg/m <sup>3</sup> )	20 mg/m <sup>3</sup>
Remark (LT)	J (jautrinantis poveikis)
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)



# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>2-hydroxyethyl methacrylate (868-77-9)</b>	
<b>Norway - Occupational Exposure Limits</b>	
Local name	2-hydroksyetylmetakrylat
Grenseverdier (AN) (mg/m <sup>3</sup> )	11 mg/m <sup>3</sup>
Grenseverdier (AN) (ppm)	2 ppm
Merknader (NO)	A (Kjemikalier som skal betraktes som at de fremkaller allergi eller annen overfølsomhet i øynene eller luftveier, eller som skal betraktes som at de fremkaller allergi ved hudkontakt)
Regulatory reference	FOR-2018-08-21-1255
<b>Ethyl alcohol (64-17-5)</b>	
<b>Austria - Occupational Exposure Limits</b>	
Local name	Ethanol
MAK (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
MAK (ppm)	1000 ppm
MAK Short time value (mg/m <sup>3</sup> )	3800 mg/m <sup>3</sup>
MAK Short time value (ppm)	2000 ppm
OEL - Ceilings (mg/m <sup>3</sup> )	3800 mg/m <sup>3</sup>
OEL - Ceilings (ppm)	2000 ppm
Regulatory reference	BGBI. II Nr. 186/2015
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Alcool éthylique # Ethanol
Limit value (mg/m <sup>3</sup> )	1907 mg/m <sup>3</sup>
Limit value (ppm)	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Етилов алкохол
OEL TWA (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.73 от 4 септември 2018 г.)
<b>Croatia - Occupational Exposure Limits</b>	
Local name	Etanol; etil-alkohol
GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
GVI (granična vrijednost izloženosti) (ppm)	1000 ppm
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Ethanol (Ethylalkohol)
Expoziční limity (PEL) (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Expoziční limity (PEL) (ppm)	530 ppm
Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>
Expoziční limity (NPK-P) (ppm)	1600 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (zpracovány změny č. 246/2018 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Ethanol (Ethylalkohol)
Grænseværdie (langvarig) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Grænseværdie (langvarig) (ppm)	1000 ppm
Regulatory reference	BEK nr 655 af 31/05/2018

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethyl alcohol (64-17-5)</b>	
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Etanool (etüülalkohol)
OEL TWA (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
OEL STEL (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OEL STEL (ppm)	1000 ppm
Regulatory reference	Vabariigi Valitsuse 18. septembri 2001. a määruse nr 293 (RT I, 30.11.2011, 5)
<b>Finland - Occupational Exposure Limits</b>	
Local name	Etanoli
HTP-arvo (8h) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
HTP-arvo (8h) (ppm)	1000 ppm
HTP-arvo (15 min)	2500 mg/m <sup>3</sup>
HTP-arvo (15 min) (ppm)	1300 ppm
Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveysministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Alcool éthylique
VME (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
VME (ppm)	1000 ppm
VLE (mg/m <sup>3</sup> )	9500 mg/m <sup>3</sup>
VLE (ppm)	5000 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
TRGS 900 Local name	Ethanol
TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	380 mg/m <sup>3</sup>
TRGS 900 Occupational exposure limit value (ppm)	200 ppm
TRGS 900 Limitation of exposure peaks	2(II)
TRGS 900 Remark	DFG;Y
TRGS 900 Regulatory reference	TRGS900
<b>Greece - Occupational Exposure Limits</b>	
Local name	Αιθνόλη
OEL TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OEL TWA (ppm)	1000 ppm
Regulatory reference	Π.Δ. 90/1999
<b>Hungary - Occupational Exposure Limits</b>	
Local name	ETIL-ALKOHOL
AK-érték	1900 mg/m <sup>3</sup>
CK-érték	7600 mg/m <sup>3</sup>
Megjegyzések (HU)	IV. (NAGYON GYENGE KÁROSÍTÓ HATÁSÚ ANYAGOK (ÁK > 500 ml/m <sup>3</sup> ))
Regulatory reference	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet a munkahelyek kémiai biztonságáról
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Ethanol
OEL (8 hours ref) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	1000 ppm

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethyl alcohol (64-17-5)</b>	
OEL (15 min ref) (ppm)	1000 ppm
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Etilspirts (etanols)
OEL TWA (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Etanolis (etilo alkoholis)
IPRV (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
IPRV (ppm)	500 ppm
TPRV (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
TPRV (ppm)	1000 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Ethanol
Grenswaarde TGG 8H (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2018
<b>Poland - Occupational Exposure Limits</b>	
Local name	Etanol (alkohol etylowy)
NDS (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Etanol (Álcool etílico)
OEL TWA (ppm)	1000 ppm
OEL STEL (ppm)	1000 ppm
OEL chemical category (PT)	A4 - Not Classifiable as a Human Carcinogen
Regulatory reference	Norma Portuguesa NP 1796:2014
<b>Romania - Occupational Exposure Limits</b>	
Local name	Alcool etilic/Etanol
OEL TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OEL TWA (ppm)	1000 ppm
OEL STEL (mg/m <sup>3</sup> )	9500 mg/m <sup>3</sup>
OEL STEL (ppm)	5000 ppm
Regulatory reference	Hotărârea nr. 584/2018
<b>Slovakia - Occupational Exposure Limits</b>	
Local name	Etylalkohol (etanol)
NPHV (priemerná) (mg/m <sup>3</sup> )	960 mg/m <sup>3</sup>
NPHV (priemerná) (ppm)	500 ppm
OEL STEL (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Ethyl alcohol (64-17-5)</b>	
OEL STEL (ppm)	1000 ppm
NPHV (Hraničná) (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	etanol (etilalkohol)
OEL TWA (mg/m <sup>3</sup> )	960 mg/m <sup>3</sup>
OEL TWA (ppm)	500 ppm
OEL STEL (mg/m <sup>3</sup> )	7600 mg/m <sup>3</sup>
OEL STEL (ppm)	4000 ppm
Remark (SI)	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
<b>Spain - Occupational Exposure Limits</b>	
Local name	Etanol (Alcohol etílico)
VLA-ED (mg/m <sup>3</sup> )	1910 mg/m <sup>3</sup>
VLA-ED (ppm)	1000 ppm
VLA-EC (mg/m <sup>3</sup> )	1910 mg/m <sup>3</sup>
VLA-EC (ppm)	1000 ppm
Notes	s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltese: Base de datos de productos biocidas: <a href="http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas">http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas</a> Base de datos de productos fitosanitarios <a href="http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf">http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf</a> ).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Etanol
nivågränsvärde (NVG) (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
nivågränsvärde (NVG) (ppm)	500 ppm
kortidsvärde (KTV) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
kortidsvärde (KTV) (ppm)	1000 ppm
Anmärkning (SE)	V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Ethanol
WEL TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
WEL TWA (ppm)	1000 ppm
WEL STEL (mg/m <sup>3</sup> )	5760 mg/m <sup>3</sup> (calculated)
WEL STEL (ppm)	3000 ppm (calculated)
Regulatory reference	EH40/2005 (Third edition, 2018). HSE
<b>Iceland - Occupational Exposure Limits</b>	
Local name	Etanól (etýlalkóhól)
OEL (8 hours ref) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
OEL (8 hours ref) (ppm)	1000 ppm
Regulatory reference	Reglugerð um mengunarmörk og aðgerðir til að draga úr mengun á vinnustöðum (Nr. 390/2009)

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl alcohol (64-17-5)	
<b>Norway - Occupational Exposure Limits</b>	
Local name	Etanol
Grenseverdier (AN) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
Grenseverdier (AN) (ppm)	500 ppm
Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	1187.5 mg/m <sup>3</sup> (value calculated)
Grenseverdier (Korttidsverdi) (ppm)	625 ppm (value calculated)
Regulatory reference	FOR-2018-08-21-1255
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Ethanol
ACGIH STEL (ppm)	1000 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2019

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection:

Impermeable protective gloves. EN 374

#### Eye protection:

Safety glasses with side shields. EN 166

#### Skin and body protection:

Long sleeved protective clothing

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: liquid.
Colour	: Pale yellow.
Odour	: Ethanol.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: > 50 °C
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

No hazardous decomposition products known at room temperature. On combustion, forms: carbon oxides (CO and CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

#### Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup> (Exposure time: 8 h)

#### Ethyl alcohol (64-17-5)

LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: This material has not been tested for environmental effects.
Acute aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)
Chronic aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)

#### Acetone (67-64-1)

LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	> 2800 mg/l 14days

Ethyl alcohol (64-17-5)	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 other aquatic organisms 1	5012 mg/l 48 hours- daphnia
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
ErC50 (algae)	275 mg/l
ErC50 (other aquatic plants)	4432 mg/l
NOEC (acute)	9.6 mg/l Daphnia magna

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Acetone (67-64-1)	
BCF fish 1	0.69
Log Pow	-0.24

Ethyl alcohol (64-17-5)	
Log Pow	-0.32

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations




### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
UN 1993	UN 1993	UN 1993	UN 1993	UN 1993
<b>14.2. UN proper shipping name</b>				
FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	Flammable liquid, n.o.s.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
<b>Transport document description</b>				
UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II, (D/E)	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II	UN 1993 Flammable liquid, n.o.s. (Ethyl alcohol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Ethyl alcohol), 3, II
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
	Not applicable	Not applicable		

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 274, 601, 640D  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02, R001  
Mixed packing provisions (ADR) : MP19  
Portable tank and bulk container instructions (ADR) : T7  
Portable tank and bulk container special provisions (ADR) : TP1, TP8, TP28  
Tank code (ADR) : LGBF  
Vehicle for tank carriage : FL  
Transport category (ADR) : 2  
Special provisions for carriage - Operation (ADR) : S2, S20  
Hazard identification number (Kemler No.) : 33  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

#### Transport by sea

Limited quantities (IMDG) : 1 L

#### Air transport

No data available

#### Inland waterway transport

Classification code (ADN) : F1  
Special provisions (ADN) : 274, 601, 640D  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E2  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01  
Number of blue cones/lights (ADN) : 1

#### Rail transport

Classification code (RID) : F1  
Special provisions (RID) : 274, 601, 640D  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E2  
Packing instructions (RID) : P001, IBC02, R001  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T7  
Portable tank and bulk container special provisions (RID) : TP1, TP8, TP28  
Tank codes for RID tanks (RID) : LGBF  
Transport category (RID) : 2  
Colis express (express parcels) (RID) : CE7



# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard identification number (RID) : 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

WGK remark : Most stringent classification due to insufficient data

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : Ethyl alcohol is listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : Ethyl alcohol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : Ethyl alcohol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Ethyl alcohol is listed

##### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Sources of Key data : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

# Superb

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 1B	H360	Calculation method

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*